



## CleanSpace<sup>®</sup> WORK Particulate Standard TM3 P3 Filter (Pk 3)



<b>PRODUCT CODE</b>	CS3002WORK
<b>PRODUCT NAME</b>	CleanSpace WORK Particulate Standard TM3 P3 Filter (Pk 3)
<b>DESCRIPTION</b>	<p>CleanSpace WORK particulate filters TM3 P3 are suitable for protection against airborne particulates (dust, mists, fumes) with a particulate filtration efficiency <math>\geq 99.95\%</math>.</p> <p>CleanSpace WORK filters are compatible with the CleanSpace WORK power unit (CS3001WORK).</p> <p><b>IMPORTANT:</b> When selecting a CleanSpace filter please consult a Health and Safety specialist for advice on the appropriate respiratory equipment and filter use.</p>
<b>APPROVALS</b>	<p>Standard &amp; Classification</p> <p>EN12942:1998+A2:2008 TM3 AS/NZS1716: 2012 PAPR-P3 (P2 with Half Mask)</p>
<b>FEATURES</b>	<ul style="list-style-type: none"> <li>• Convenient to use <ul style="list-style-type: none"> <li>◦ Filter and filter cover integrated into a single item</li> <li>◦ Easy to fit and remove from the power unit</li> <li>◦ No requirement for a filter adaptor</li> </ul> </li> <li>• AirSensit™ Technology assists with optimal filter usage.</li> </ul>
<b>SPECIFICATIONS</b>	<ul style="list-style-type: none"> <li>• Packaged Weight &amp; Dimensions: 123 g, 180mm x 160mm x 50mm (3 Pack)</li> <li>• Product Weight &amp; Dimensions: 29 g, 24mm x 47mm x 130mm (single filter)</li> <li>• Filtration performance: <math>\geq 99.95\%</math> filtration efficiency for particulates</li> <li>• Sold in a pack of 3 filters</li> </ul>
<b>MATERIALS</b>	Borosilicate microfibre media   ABS (acrylonitrile butadiene styrene) Plastic Casing   Polyurethane Seal
<b>USE &amp; STORAGE CONDITIONS</b>	<ul style="list-style-type: none"> <li>• Use temperature range: -10°C to +45°C (14°F to +113°F) at &lt; 90% relative humidity</li> <li>• Storage conditions: +10°C to +30°C (+50°F to +86°F) at &lt; 75% relative humidity</li> <li>• Store away from direct sunlight, grease and oil</li> <li>• Packaged Shelf life: 5 years from manufacturing date</li> </ul>
<b>APPLICATIONS</b>	Suitable for environments which require respiratory protection against airborne particulate contaminants.

Australia (Head Office): +61 2 8436 4000 | [sales@cleanspacetechnology.com](mailto:sales@cleanspacetechnology.com)

*Uncontrolled if downloaded or printed from the internet.*

**WWW.CLEANSPACETECHNOLOGY.COM**





Examples (use is not limited to these examples):

- Construction – Cutting and grinding concrete, stone, brickwork, steel; sanding plaster, handling cement or other fine dusts
- Woodwork – Cutting, turning or sanding timber
- Agriculture – mowing, reaping and mulching operations; processing or handling animal feeds, grain or other dusty substances

The CleanSpace WORK System (CS3000WORK) is suitable for applications where decontaminations showers are used.

**LIMITATIONS**

CleanSpace respirators are air filtering, fan assisted, positive pressure systems and designed to be worn in environments where there is sufficient oxygen to breathe safely. Do not use CleanSpace WORK in environments that are immediately dangerous to life or health (IDLH), to protect against gases/vapours, or in oxygen enriched or deficient atmospheres.

**EDUCATION**

Contact [sales@cleanspacetechnology.com](mailto:sales@cleanspacetechnology.com) or visit the [CleanSpace website](https://www.cleanspacetechnology.com) for details.

**WARRANTY**

Visit [www.cleanspacetechnology.com/warranty](https://www.cleanspacetechnology.com/warranty) to read important Warranty information and complete the Warranty Registration Online Form for CleanSpace Products. Consumable parts are warranted up to the point of use, provided they have been stored correctly and are within their expiry date.

CleanSpace recommends filters are replaced regularly.

