



## CleanSpace<sup>®</sup> Combined Filter AX P2 TM2 Filter



<b>PRODUCT CODE</b>	PAF-0087
<b>PRODUCT NAME</b>	CleanSpace Combined Filter AX P2 TM2 (NR SL)
<b>DESCRIPTION</b>	<p>The CleanSpace Combined Filter AX P2 TM2 (SL NR) is suitable for protection against airborne particulates (dust, mists and fumes) as well as certain low boiling point (<math>\leq 65^{\circ}\text{C}</math>) organic compounds such as methyl bromide, methanol, acetone. Filtration efficiency is greater than 99.95% for <math>0.3\mu\text{m}</math> particles or above.</p> <p>The PAF-0087 filter is single use only and must be replaced after each use.</p> <p><b>IMPORTANT:</b> When selecting a CleanSpace filter please consult a Health and Safety specialist for advice on the appropriate respiratory equipment and filter use.</p>
<b>APPROVALS</b>	<p>Standard &amp; Classification</p> <p>EN12942:1998+A2:2008 TM2AXP NR SL AS/NZS1716: 2012 PAPR-AXP2</p>
<b>FEATURES</b>	<ul style="list-style-type: none"><li>• Convenient to use with CleanSpace2, CleanSpace ULTRA and CleanSpace EX Power Units.</li><li>• Used with the revolutionary CleanSpace - A light weight PAPR with no hoses/belts.</li><li>• Suitable for protection against airborne particulates (dust, mists and fumes) as well as certain low boiling point (<math>\leq 65^{\circ}\text{C}</math>) organic compounds (e.g. methanol, acetone, methyl bromide).</li><li>• Easily fitted and removed from the Power Unit.</li></ul>
<b>SPECIFICATIONS</b>	<ul style="list-style-type: none"><li>• Product Weight &amp; Dimensions: 300g, 170mm x 80mm x 65mm</li><li>• Must be used with a CleanSpace Filter Adaptors PAF-0038 or PAF-0078 (EX).</li><li>• The filter is single use only and must be replaced after each use.</li><li>• The filter should be replaced if filter media has come in contact with water</li></ul>
<b>MATERIALS</b>	Fibreglass particulate and carbon media in ABS case.
<b>USE &amp; STORAGE CONDITIONS</b>	<ul style="list-style-type: none"><li>• Use temperature range: <math>-10^{\circ}\text{C}</math> to <math>+45^{\circ}\text{C}</math> (<math>14^{\circ}\text{F}</math> to <math>+113^{\circ}\text{F}</math>) at <math>&lt; 90\%</math> relative humidity</li><li>• Storage Conditions:<ul style="list-style-type: none"><li>○ Short Term (<math>&lt; 30</math> days): <math>-10^{\circ}\text{C}</math> to <math>+35^{\circ}\text{C}</math> (<math>14^{\circ}\text{F}</math> to <math>95^{\circ}\text{F}</math>)</li><li>○ Long Term (<math>&gt; 30</math> days): <math>+18^{\circ}\text{C}</math> to <math>+28^{\circ}\text{C}</math> (<math>64^{\circ}\text{F}</math> to <math>82^{\circ}\text{F}</math>)</li><li>○ 30% - 50% relative humidity</li><li>○ Out of direct sunlight, in a clean, dry environment</li></ul></li><li>• Packaged Shelf life: 5 years from manufacturing date</li></ul>





**APPLICATIONS**

Handling of organic chemicals with low boiling point in sectors including chemical processing; Pharmaceutical production; Manufacturing; Aerospace; Energy, Oil & Gas; Industrial fumigation.

**LIMITATIONS**

The CleanSpace Combined Filter AX P2 TM2 (SL NR) is for single use only and must be replaced after each use.

CleanSpace respirators are air filtering, fan assisted, positive pressure systems and designed to be worn in environments where there is sufficient oxygen to breathe safely. Do not use CleanSpace respirators in environments that are immediately dangerous to life or health (IDLH), to protect against gases/vapours that cannot be filtered or in oxygen enriched or deficient atmospheres.

**EDUCATION**

Contact [sales@cleanspacetechnology.com](mailto:sales@cleanspacetechnology.com) or visit the [CleanSpace website](#) for details.

**WARRANTY**

Visit [www.cleanspacetechnology.com/warranty](http://www.cleanspacetechnology.com/warranty) to read important Warranty information and complete the Warranty Registration Online Form for CleanSpace Products. Consumable parts are warranted up to the point of use, provided they have been stored correctly and are within their expiry date.

