



## CleanSpace<sup>®</sup> Half Mask Fit Test Kit



**PRODUCT CODE**

PAF-1043

**PRODUCT NAME**

CleanSpace Half Mask Fit Test Kit

**DESCRIPTION**

The CleanSpace Half Mask Fit Test Kit consists of the following items:

- 1 x PAF-0025 Half Mask Fit Testing Adaptor
- 6 x PAF-1036 CleanSpace Grommets

Please refer to the data sheets on the following pages for further information.





## CleanSpace<sup>®</sup> Half Mask Fit Testing Adaptor



<b>PRODUCT CODE</b>	PAF-0025
<b>PRODUCT NAME</b>	CleanSpace Half Mask Fit Testing Adaptor
<b>DESCRIPTION</b>	<p>The CleanSpace Half Mask Fit Testing Adaptor is designed to be used with all CleanSpace Half Masks. The Half Mask adaptor is fitted in the front of the Half Mask to enable a Quantitative Fit Test.</p> <p>Instructions for use are provided with the adaptor.</p>
<b>FEATURES</b>	<ul style="list-style-type: none"> <li>• Reuseable</li> </ul>
<b>SPECIFICATIONS</b>	<ul style="list-style-type: none"> <li>• Product Weight: 25 g</li> <li>• Product Dimensions: 51mm x 37mm x 21mm (approx)</li> </ul>
<b>MATERIALS</b>	Aluminium   Nylon O-Ring   Brass Pressure Port
<b>OPERATING / USAGE CONDITIONS</b>	<ul style="list-style-type: none"> <li>• Use temperature range: -10°C to +45°C (14°F to +113°F) at &lt; 90% relative humidity</li> </ul>
<b>STORAGE &amp; DISPOSAL</b>	<ul style="list-style-type: none"> <li>• Storage conditions: +10°C to +30°C (+50°F to +86°F) at &lt; 75% relative humidity</li> <li>• Store away from direct sunlight, grease and oil</li> <li>• Used components may have been exposed to hazardous materials and should not be considered recyclable. Dispose of used components in line with company and local authority regulations.</li> </ul>
<b>CLEANING</b>	<ul style="list-style-type: none"> <li>• Hand wash in warm (&lt; 50°C) soapy water and rinse<sup>1</sup></li> <li>• Do not use solvents, hot water, bleaching or chemical agents</li> <li>• After cleaning allow to air dry or wipe dry with a clean lint free cloth</li> </ul> <p>Note 1: Refer to Supplements for compatible cleaning products and industrial washing processes.</p>
<b>LIMITATIONS</b>	CleanSpace respirators are air filtering, fan assisted, positive pressure systems and designed to be worn in environments where there is sufficient oxygen to breathe safely. Do not use CleanSpace respirators in immediately dangerous to life or health (IDLH) atmospheres, to protect against gases/vapours that cannot be filtered or in oxygen enriched or deficient atmospheres.
<b>EDUCATION</b>	Contact <a href="mailto:sales@cleanspacetechnology.com">sales@cleanspacetechnology.com</a> or visit the <a href="#">CleanSpace website</a> for details.
<b>WARRANTY</b>	Visit <a href="http://www.cleanspacetechnology.com/warranty">www.cleanspacetechnology.com/warranty</a> to read important Warranty information and complete the Warranty Registration Online Form for CleanSpace Products. Consumable parts are warranted up to the point of use, provided they have been stored correctly and are within their expiry date.





## CleanSpace<sup>®</sup> Grommets (6 Pk)



<b>PRODUCT CODE</b>	PAF-1036
<b>PRODUCT NAME</b>	CleanSpace Grommets
<b>DESCRIPTION</b>	<p>CleanSpace Grommets are an optional accessory for use during fit testing and are designed for use with all CleanSpace Half Masks. Grommets are inserted into each arm of the CleanSpace Half Mask to ensure that exhaled air exits the CleanSpace Half Mask through the Exhalation Valve in the front of the mask during Fit Testing.</p> <p><b>IMPORTANT:</b> CleanSpace Grommets should only be fitted whilst Fit Testing is being conducted. Failure to remove the CleanSpace Grommets during normal use may result in decreased run times.</p>
<b>FEATURES</b>	<ul style="list-style-type: none"> <li>• Prevents the wearers breath travelling rearward during fit testing.</li> <li>• Grommets have no adverse affect on fit test results.</li> <li>• Reusable.</li> </ul>
<b>SPECIFICATIONS</b>	<ul style="list-style-type: none"> <li>• Product Weight (1 grommet): 4 g</li> <li>• Package Weight (6 grommets): 30 g</li> <li>• Product Dimensions: 67mm x 45mm x 18mm (approx)</li> </ul>
<b>MATERIALS</b>	Nylon   Silicone Valve
<b>OPERATING / USAGE CONDITIONS</b>	<ul style="list-style-type: none"> <li>• Use temperature range: -10°C to +45°C (14°F to +113°F) at &lt; 90% relative humidity</li> </ul>
<b>STORAGE &amp; DISPOSAL</b>	<ul style="list-style-type: none"> <li>• Storage conditions: +10°C to +30°C (+50°F to +86°F) at &lt; 75% relative humidity</li> <li>• Store away from direct sunlight, grease and oil</li> <li>• Used components may have been exposed to hazardous materials and should not be considered recyclable. Dispose of used components in line with company and local authority regulations.</li> </ul>
<b>CLEANING</b>	<ul style="list-style-type: none"> <li>• Hand wash in warm (&lt; 50°C) soapy water and rinse<sup>1</sup></li> <li>• Do not use solvents, hot water, bleaching or chemical agents</li> <li>• After cleaning allow to air dry or wipe dry with a clean lint free cloth</li> </ul> <p>Note 1: Refer to Supplements for compatible cleaning products and industrial washing processes.</p>
<b>APPLICATIONS</b>	Fit Testing applications only - <b>Do not</b> use Grommets for normal operations.





**LIMITATIONS**

CleanSpace respirators are air filtering, fan assisted, positive pressure systems and designed to be worn in environments where there is sufficient oxygen to breathe safely. Do not use CleanSpace respirators in environments that are immediately dangerous to life or health (IDLH), to protect against gases/vapours that cannot be filtered or in oxygen enriched or deficient atmospheres.

**EDUCATION**

Contact [sales@cleanspacetechnology.com](mailto:sales@cleanspacetechnology.com) or visit the [CleanSpace website](#) for details.

**WARRANTY**

Visit [www.cleanspacetechnology.com/warranty](http://www.cleanspacetechnology.com/warranty) to read important Warranty information and complete the Warranty Registration Online Form for CleanSpace Products. Consumable parts are warranted up to the point of use, provided they have been stored correctly and are within their expiry date.

