



CleanSpace™ EX / ULTRA Full Face Mask



PRODUCT CODE	PAF-1106 (Small), PAF-1014 (Medium/Large)
PRODUCT NAME	CleanSpace ULTRA / EX Full Face Mask
DESCRIPTION	<p>A CleanSpace ULTRA / EX Full Face Mask is designed for use with the CleanSpace EX Power Unit (PAF-2060) and CleanSpace ULTRA Power Unit (PAF-2070).</p> <p>A CleanSpace ULTRA / EX Full Face Mask has a wide, soft, silicone seal that readily molds to the face and does not cause allergic dermatitis. The clips quickly and securely attach the CleanSpace ULTRA / EX Full Face Mask to the Power Unit.</p>
APPROVALS	<p>Standard & Classification</p> <p>NIOSH Approved</p>
FEATURES	<ul style="list-style-type: none"> • Visor: Scratch-resistant and solvent-resistant coating • Wide panoramic visor • Silicone cushion seals to the face for optimum protection and comfort • Recommended for applications where face protection and eye protection is required • Suitable for long periods of wear • Mylar speech diaphragm for clear communication • Positive pressure airflow prevents fogging • Inner mask has a unique clip-in/clip-out design and is easily removed for cleaning • Built in port and sensing ball included for TSI Portacount full face mask fit testing • Accessories available (sold separately): Spectacle kit and visor protection tear-offs
SPECIFICATIONS	<ul style="list-style-type: none"> • Product Weight: PAF-1106:700 g (Small), PAF-1014:725 g (Medium/Large) • Product Dimensions: 240mm x 220mm x 280mm (approx)
MATERIALS	Hard coated polycarbonate visor nylon mask clips high strength silicone harness stainless steel buckle roller silicone face seal and inner mask cushion Mylar speech diaphragm polycarbonate exhalation valve cover impact-modified reinforced polypropylene exhalation valve housing silicone O-rings
CLEANING, USE & STORAGE CONDITIONS	<ul style="list-style-type: none"> • Cleaning: warm soapy water and soft, lint-free cloth or industrial washer • Do not use solvents, hot water, bleaching or chemical agents • Use temperature range: -10°C to +45°C (14°F to +113°F) at < 90% relative humidity • Storage conditions: +10°C to +30°C (+50°F to +86°F) at < 75% relative humidity • Store away from direct sunlight, grease and oil

Australia (Head Office): +61 2 8436 4000 | sales@cleanspacetechnology.com

Uncontrolled if downloaded or printed from the internet.

WWW.CLEANSPEACEUSA.COM





APPLICATIONS

Suitable for environments which require respiratory protection against airborne biohazards, particulates and dust.

Examples: Mining, blasting, grinding, drilling, or crushing. Tunnelling, excavation, rock and mineral handling.

The CleanSpace EX System (PAF-2060) and the CleanSpace ULTRA System (PAF-2070), with the CleanSpace ULTRA / EX Full Face Mask are suitable for applications where decontaminations showers are required.

LIMITATIONS

CleanSpace respirators are air filtering, fan assisted, positive pressure systems and designed to be worn in environments where there is sufficient oxygen to breathe safely. Do not use CleanSpace respirators in immediately dangerous to life or health (IDLH) atmospheres, to protect against gases/vapours that cannot be filtered or in oxygen enriched or deficient atmospheres.

EDUCATION

Contact sales@cleanspacetechnology.com or visit the [CleanSpace website](#) for details.

WARRANTY

Visit <https://cleanspacetechnology.com/warranty/> to read important Warranty information and complete the Warranty Registration Online Form for CleanSpace Products. Consumable parts are warranted up to the point of use, provided they have been stored correctly and are within their expiry date. CleanSpace recommends filters are replaced regularly.

