

PRODUCT CODES: PAF-0014 (Thick) and PAF-0016 (Thin)

PRODUCT NAMES: CleanSpace2™ Neck Pads Thick (Spare)

CleanSpace2™ Neck Pads Thin (Spare)



Description

The CleanSpace Neck Pads are designed to be used with CleanSpace2 Respirators (PAF-1034 & PAF-2034). The Neck Pads (thick and thin) are sold with every CleanSpace2 unit and available as spares in case of damage or loss. The Neck Pads are made of foam with neoprene (fabric) covering and can be attached to the unit using Velcro strips.

IMPORTANT: These neck pads are fabric with Velcro and should NOT be used when handling friable asbestos or in Intrinsically Safe certified zones.

Approvals

Standards

NIOSH Approved
EN 12942 (CE Mark)
AS/NZS1716: 2012

Classification

PAPR-High Efficiency (HEPA) Particulate

Features

- Used with the CleanSpace2 Respirators: light weight, no hoses or belts
- Designed for comfort over long periods
- Allows sweating and offers breathability
- Easy to wash and quick drying; quick to replace
- Designed for long wear in harsh environments
- Hygienic (medical quality materials) and hypoallergenic

Specifications and materials

- Weight: 8g (thin) and 20g (thick)
- Dimensions: 163mm x 95mm x 5mm (thin) – x 30mm (thick)
- Cleaning: Lukewarm water and mild detergent (neutral pH 6 – 8). Do not use solvents (turpentine or acetone), hot water, bleaching or chemical agents.
- Storage: –10°C to +55°C (–4°F to +131°F) at <90% relative humidity. Store away from direct sunlight, grease and oil.
- Only to be used with the CleanSpace2™ PAPR power units

Suitable Applications

Welding, Woodworking, Manufacturing, Smelting, Construction, Recycling Plants, Emergency Services, Mining, Agriculture, Processing Plants, Grinding, DIY, etc.

Training

Online training available with verification for compliance purposes.
Contact sales@paftec.com.

Limitations

CleanSpace respirators are air filtering, fan assisted positive pressure masks and designed to be worn in environments where there is sufficient oxygen to breathe safely. Do not use the CleanSpace in IDLH atmospheres, to protect against gases/vapours that cannot be filtered, or in Oxygen enriched or deficient atmospheres.